



EQUIPMENT SPECIFICATIONS

22 x 160W Canopy Lamps: Bench Lamps: 16 x 180W 3 x 400W Facial: Session Time: 12 Minutes Room AC Requirements: BTU 9000 A/C

Recommended Room Size: 9 x 9 ft

91" x 46" x 65" Shipping Dimensions:

Shipping Weight: 975 lbs

Dimensions: 90.2"L x 53.5"W x 61.4"H

STANDARD FFATURES

T-Max Integration w/ Quickstart Connection **Touch Screen User Display** Adjustable Body and Facial Cooling **Ambient Flowlight Contoured Acrylic** SoundAround Music System w/ Bluetooth

ELECTRICAL REQUIREMENTS

Three Phase Connection

Electrical Rating: 230V 3~28A 60 Hz; 3 Pole

(3 Hots, 1 Ground)

Breaker Size: 40 Amp Buckbooster: 2 * 1.0 Kva

Single Phase Connection

Electrical Rating: 230V ~45A 60 Hz; 2 Pole

(2 Hots, 1 Ground)

Breaker Size: 60 Amp **Buckbooster:** 1 * 1.5 Kva

Note: Equipment comes standard in three phase configuration. Buckboosters must be installed by licensed electrician in your state/county.

Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product must not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer."

*ProSun reserves the right to change design and specifications without notice.

510(K): K181455

