LUXURA X3 HYBRID ()12 Minutes

EQUIPMENT SPECIFICATIONS

Canopy Lamps:
Bench Lamps:
Facial:
Session Time:
Room AC Requirements:
Recommended Room Siz
Shipping Dimensions:
Shipping Weight:
Dimensions:

ProTech UV - 14 x 160W RenuvaTan Red Light - 6 x 200W ProTech UV - 12 x 180W RenuvaTan Red Light 4 x 200W XL 3 x 400W 12 Minutes BTU 6000 A/C ze: 9 x 9 ft 91" x 46" x 55" 675 lbs 90.2"L x 47.6"W x 61.4"H

STANDARD FEATURES

T-Max Integration w/ Quickstart Connection Adjustable Body Cooling SoundAround Music System

ELECTRICAL REQUIREMENTS

Three Phase Connection

Electrical Rating:	230V 3~22A 60 Hz; 3 Pole
	(3 Hots, 1 Ground)
Breaker Size:	30 Amp
Buckbooster:	2 * 0.75 Kva

Single Phase Connection

Electrical Rating:	230V ~35A 60 Hz; 2 Pole
	(2 Hots, 1 Ground)
Breaker Size:	40 Amp
Buckbooster:	1 * 1.0 Kva

Note: Equipment comes standard in three phase configuration. Buckboosters must be installed by licensed electrician in your state/county.

Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This produc should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer."

*ProSun reserves the right to change design and specifications without notice.

• 510(K): K181455 •





