

LUXURA V8 HYBRID









EQUIPMENT SPECIFICATIONS

ProTech UV - 36 x 200W Lamps:

RenuvaTan Red Light - 12 x 200W

Session Time: 8 Minutes **Room AC Requirements:** BTU 12000 A/C

Recommended Room Size: 8 x 7 ft

91" x 46" x 72" **Shipping Dimensions:**

750 lbs **Shipping Weight:**

Dimensions: 59"D x 77.2"W x 92.5"H

STANDARD FFATURES

Electronic Ballasts

T-Max Integration w/ Quickstart Connection

Touch Screen User Display Adjustable Body Cooling Sound System w/ Bluetooth

Optional Upgrades:

Dressing Room



Three Phase Connection

Electrical Rating: 230V 3~23A 60 Hz; 3 Pole

(3 Hots, 1 Ground)

Breaker Size: 30 Amp **Buckbooster:** 2 x 0.75 Kva

Single Phase Connection

230V~40A 60 Hz: 2 Pole **Electrical Rating:**

(2 Hots, 1 Ground)

Breaker Size: 50 Amp **Buckbooster:** 1 x 1.5 Kva

Note: Equipment comes standard in three phase configuration. Buckboosters must be installed by licensed electrician in your state/county.

Contraindication: This product is contraindicated for use on persons under the age of 18 years. "Contraindication: This product must not be used if skin lesions or open wounds are present." "Warning: This product should not be used on individuals who have had skin cancer or have a family history of skin cancer." "Warning: Persons repeatedly exposed to UV radiation should be regularly evaluated for skin cancer."

*ProSun reserves the right to change design and specifications without notice

• 510(K): K181455 •





